T21



Full Keyboard Rugged Handheld





T21

Full Keyboard Rugged Handheld

T21, the full keyboard rugged handheld has a combination of connectivity options and standard features, including DB9 series port, Wi-Fi and 3G/4G, provides entire solutions for high-accuracy GIS applications. The fully-rugged IP rate is designed for field use. T21 come ready for you with application possibilities in power companies, agriculture and geological industries, forestry, field service, GIS/surveying and so on.







Specification

| | Item | T21 | T218P | T219P |
|-------------------------------------|---------------------------|---|-------------|---|
| Overview | Processor | 1GHZ | | |
| | RAM | 512M | | |
| | ROM | 1GB | | |
| | Operation System | Windows Embedded Handheld | | |
| | Camera | 5 megapixel | | |
| | Keypad | 62 numeric + programmable keys | | |
| | Display | 5" sunlight readable with integrated touch screen 800*480 | | |
| | Dimension | 283mm × 158mm × 50mm | | |
| GNSS Performance | GNSS Module | ublox M8N | ublox M8P | ublox F9P |
| | GNSS (Optional) | GPS L1+BD L1/GPS L1+GLONASS L1 | | GPS L1, L2/GLONASS G1, G2 /Beidou B1, B2/GALILEO E1, E5 |
| | Channels | 72 | 72 | 184 |
| | Raw Data | Alternative | | |
| | NMEA-0183 | \checkmark | √ | \checkmark |
| | Rove/Base | - | Alternative | Alternative |
| Accuracy (Internal Accord accuracy) | Autonomous | 2.5m | 2.5m | 1.5m |
| | SBAS | 2m | - | - |
| | RTK | - | 2.5cm+1ppm | 1cm+1ppm |
| Communications and Data Storage | WIFI | \checkmark | | |
| | USB port | 1* B Type Client, 1*A Type Host | | |
| | Serial port | DB9 | | |
| | Storage extension | TF card | | |
| | Long range Bluetooth | Optional (along with standard bluetooth) | | |
| | Bluetooth | V2.1 | | |
| | Datalink | 3G | | |
| Power | DC input | DC 5V, 2A | | |
| | Detachable Li-ion battery | 6500mAh, 3.7V | | |
| | Working time | >8h | | |
| Environment Specification | Operating temperature | - 30℃ ~+60℃ | | |
| | Storage temperature | - 30°C ~ +80°C | | |
| | Sand, dust&water | IP65 | | |
| | Drop | 1.2m protection | | |
| Supported Software | Supported Software | SurvCE, FieldGenius, SuperGeo | | |





